

## Standard Flexible Couplings



Fernco's specially formulated PVC compound positively seals most sewer and drain connections.

Fernco makes the most complete line of couplings in the industry, from sizes 3/4" and larger. Custom large diameter couplings are available, along with shielded transitional couplings to ensure all pipes, underground and above-ground, can be connected with a Fernco coupling. Because Fernco couplings have earned a reputation for superior performance, you can have full confidence in their quality and reliability.

Tested designs backed by over five decades of proven experience

Available from 3/4" and larger

- Seals against infiltration and exfiltration
- Leak-proof, root-proof and resistant to many chemicals, ultra violet rays, fungus growth and normal sewer gas
- Conforms to ASTM D 5926, C 1173 and CSA B602
- Connects pipes of same or different materials and sizes
- Corrosion-resistant and rust-proof stainless steel clamps
- Made of elastomeric polyvinyl chloride (PVC)
- 4.3 PSI maximum test pressure
- 140°F maximum intermittent operating temperature
- 120°F maximum consistent operating temperature



## High Torque Clamps

STANDARD on all 18" and larger couplings



Flexible Couplings

see sizes on pg. 17-24

## 1055 Series Couplings

AC or DI to AC or DI

\* Insert bushing included **Red** high torque clamps included   new

<b>15" x 12" (375 mm x 300 mm)</b>	16.80 x 13.20 <b>1055-1512*</b>	16.80 x 13.20 <b>1055-1512RC*</b>	16.80 x 13.20 <b>1055-1512EB</b>
<b>15" x 15" (375 mm x 375 mm)</b>	16.80 x 16.80 <b>1055-1515</b>	16.30 x 16.30 <b>1055-1515RC</b>	
<b>18" x 18" (450 mm x 450 mm)</b>	19.70 x 19.70 <b>1055-1818</b>	19.70 x 19.70 <b>1055-1818RC</b>	
<b>24" x 24" (600 mm x 600 mm)</b>	25.80 x 27.31 <b>1055-2424</b>	25.80 x 27.31 <b>1055-2424RC</b>	

## 1056 Series Couplings

Cl, Plastic, Copper, Steel or Lead to Cl, Plastic, Copper, Steel or Lead

NOMINAL PIPE DIAMETER	STANDARD	STRONG BACK 1000 RC SERIES	STRONG BACK 5000 RC SERIES	ECCENTRIC
<b>0.75" x 0.75" (19 mm x 19 mm)</b>	1.05 x 1.05 <b>1056-075</b>			
<b>1" x 1" (25 mm x 25 mm)</b>	1.31 x 1.31 <b>1056-100</b>			
<b>1.25" x 1.25" (32 mm x 32 mm)</b>	1.63 x 1.63 <b>1056-125</b>			
<b>1.50" x 1.25" (38 mm x 32 mm)</b>	1.94 x 1.63 <b>1056-150/125</b>			
<b>1.5" x 1.50" (38 mm x 38 mm)</b>	1.94 x 1.94 <b>1056-150</b>	1.94 x 1.94 <b>1056-150RC</b>		
<b>2" x 1.50" (51 mm x 38 mm)</b>	2.41 x 1.84 <b>1056-215</b>	2.41 x 1.84 <b>1056-215RC</b>		
<b>2" x 2" (51 mm x 51 mm)</b>	2.41 x 2.41 <b>1056-22</b>	2.41 x 2.41 <b>1056-22RC</b>		
<b>2.50" x 1.25" (64 mm x 32 mm)</b>	2.88 x 1.63 <b>1056-250/125</b>	2.88 x 1.63 <b>1056-250/125RC</b>		
<b>2.50" x 1.50" (64 mm x 38 mm)</b>	2.88 x 1.84 <b>1056-250/150</b>	2.88 x 1.84 <b>1056-250/150RC</b>		
<b>2.50" x 2" (64 mm x 51 mm)</b>	2.88 x 2.38 <b>1056-250/22</b>	2.88 x 2.38 <b>1056-250/22RC</b>		
<b>2.50" x 2.50" (64 mm x 64 mm)</b>	2.88 x 2.88 <b>1056-250</b>	2.88 x 2.88 <b>1056-250RC</b>		
<b>3" x 1.50" (76 mm x 38 mm)</b>	3.35 x 1.91 <b>1056-315</b>			3.46 x 1.90 <b>1056-315EB</b>
<b>3" x 2.50" (76 mm x 64 mm)</b>	3.55 x 2.88 <b>1056-3/250</b>	3.55 x 2.88 <b>1056-3/250RC</b>		
<b>3" x 3" (76 mm x 76 mm)</b>	3.46 x 3.46 <b>1056-33</b>	3.46 x 3.46 <b>1056-33RC</b>	3.46 x 3.46 <b>5056-33RC</b>	
<b>4" x 1.50" (100 mm x 38 mm)</b>	4.39 x 1.91 <b>1056-415</b>			
<b>4" x 4" (100 mm x 100 mm)</b>	4.58 x 4.58 <b>1056-44</b>	4.58 x 4.58 <b>1056-44RC</b>	4.58 x 4.58 <b>5056-44RC</b>	
<b>5" x 4" (125 mm x 100 mm)</b>	5.57 x 4.26 <b>1056-54</b>	5.52 x 4.38 <b>1056-54RC</b>	5.52 x 4.38 <b>5056-54RC</b>	5.52 x 4.50 <b>1056-54EB</b>
<b>5" x 5" (125 mm x 125 mm)</b>	5.52 x 5.52 <b>1056-55</b>	5.52 x 5.52 <b>1056-55RC</b>	5.52 x 5.52 <b>5056-55RC</b>	
<b>6" x 4" (150 mm x 100 mm)</b>	6.61 x 4.46 <b>1056-64</b>	6.60 x 4.50 <b>1056-64RC*</b>	6.60 x 4.50 <b>5056-64RC*</b>	6.60 x 4.50 <b>1056-64EB</b>
<b>6" x 5" (150 mm x 125 mm)</b>	6.48 x 5.46 <b>1056-65</b>	6.60 x 5.62 <b>1056-65RC</b>	6.60 x 5.62 <b>5056-65RC</b>	6.60 x 5.50 <b>1056-65EB</b>